

Glazed Sliding Doors

8. B15 GLAZED SLIDING DOOR, DELI, single, automatic or manual

Fire class	B15	
Max frame size	1460 x 2595 mm (max. area 3,15 m ²)	
Glass sound insulation (dB)	40	
Certificate no.	EUFI29-19003649	
Standard accessories	Automatic version <ul style="list-style-type: none"> the necessary auxiliary equipment (see page Automatic doors) 	Manual version <ul style="list-style-type: none"> Lock TrioVing 5049 Pull Sliding rail and roller assemblies Speed limiter (option)

Notes	<ul style="list-style-type: none"> Both for interior and exterior use No sill Available with different automatic mechanisms The automatic version does not include a mechanical lock Available as pocket or non-pocket versions (slides into the wall or on the wall surface) Door construction is fire tested from both sides with cable penetration. Glass wall can continue as a continuous wall straight from the door without an intermediate bulkhead Note the need for a sufficiently large service hatch to maintain the mechanism
-------	--

To order please specify:

- door dimensions
- frame finish
- grids and patterns
- pull (for manual version)
- pocket or non-pocket version
- door use purpose
- handing as viewed from the mechanism side
- interior / exterior / wet room
- manual or automatic operation
- desired automatic system
- other special requirements
- possible evacuation route (Exit and ADA rules)

