

Glazed Sliding Doors

9. B15 GLAZED SLIDING DOOR DELI, double, automatic or manual

Fire class	B15	
Max frame size	1322 + 1322 x 2584 mm (max area 5,7 m ²)	
Glass sound insulation (dB)	40	
Certificate no.	EUFI29-21002966-MED (B+D)	
Standard accessories	Automatic version <ul style="list-style-type: none"> • Automatic mechanism with the necessary auxiliary equipment (see page Automatic doors) 	Manual version <ul style="list-style-type: none"> • Lock TrioVing 5049 • Pull • Sliding rail and roller assemblies • Speed limiter (option)

Notes	<ul style="list-style-type: none"> • Both for interior and exterior use • No sill • Available with different automatic mechanisms • The automatic version does not include a mechanical lock • Available as pocket or non-pocket versions (slides into the wall or on the wall surface) • Door construction is fire tested from both sides with cable penetration. • Glass wall can continue as a continuous wall straight from the door without an intermediate bulkhead • Note the need for a sufficiently large service hatch to maintain the mechanism
-------	--

To order please specify:

- door dimensions
- frame finish
- grids and patterns
- pull for manual version
- pocket or non-pocket version
- door use purpose
- handing as viewed from the mechanism side
- interior / exterior / wet room
- manual or automatic operation
- desired automatic system
- other special requirements
- possible evacuation route (Exit and ADA rules)

